



**Australia's Most  
Beautiful Floors**



## Genuine Appalachian Hickory

Elk Falls Hickory planks are manufactured from genuine North American Appalachian Hickory. It is an excellent durable hardwood ideally suited to flooring installations where strength & impact resistance are important considerations. Elk Falls Hickory flooring, a great choice for the rough and tumble of everyday life.



SMOKEY PEAT



“  
*Hickory Hardwood,  
It's Hard to Beat!*”



TOASTED RYE



MORNING MIST



MOONSHINE





## Details That Matter

Elk Falls Hickory flooring provides a unique set of characteristics that make it ideal for use in residential homes, apartments and for commercial applications.

Hickory has been used for centuries in applications where its inherent strength and stiffness have been considered a major advantage in applications from timber engineered elements, cabinetry, sporting goods to everyday products such as axe handles. Hickory is extremely stable with excellent hardness characteristics, approx 9.5kN JANKA scale, similar to popular Australian timbers, Blackbutt and Jarrah.

- Engineered construction, Unilin patented click profile.
- Wear resistant pre-finished European water-based UV lacquer, matte sheen level.
- Hickory rustic grade, a natural look with lots of character and appeal.
- Visual appearance will suit those seeking a classic hardwood in a range of natural or stained décors.
- VOC emissions: <E1. Below World Health Organisation (WHO) levels. Allergy free.
- Australian fire and slip test certified. Suitable for install over hydronic in-slab heating only.




NATURAL

COLOUR RANGE

# 1900 x 189 x 14mm

2mm solid hickory wear layer

1900mm set length & nested shorts approx. 30%





TOASTED RYE



RUSTIC NATURAL

## Technical Specifications

### DESCRIPTION

Engineered multi-layer construction, solid hickory wear layer.

### GRADE & SURFACE

A/B/C/D grade. Allows for rustic features, contains knots & splits that are filled to complement surface colour and character along with sapwood, raised grain and colour streaks that enhance its rustic charm. Light brushed surface, pre-finished European PU matte coating. P3 slip test certified.

### PROFILE

Micro bevelled edges. Unilin patented click for fast and efficient floating install.

### ACOUSTIC TEST OUTCOME

Sample installed on 2mm Ultra Green Underlay	NCC/BCA criterion	Test result L'nT,w	AAAC <sup>5</sup> star rating	FIIIC <sup>4,5</sup>	Compliance with NCC/BCA
14mm Hickory Timber	L'nT,w<62	42 ✓	5	63	Yes ✓



**Preference Floors (SA)**  
Adelaide  
08 8262 2774  
sa@preferencefloors.com.au

**Preference Floors (QLD)**  
Brisbane  
07 3875 1688  
qld@preferencefloors.com.au

**Preference Floors (VIC)**  
Melbourne  
03 9794 5111  
vic@preferencefloors.com.au

**Preference Floors (WA)**  
Perth  
08 9471 7785  
wa@preferencefloors.com.au

**Preference Floors (NSW)**  
Sydney  
02 9738 1188  
sales@preferencefloors.com.au

PREFERENCE  FLOORS  
www.preferencefloors.com.au