

NFD Hybrid Flooring Safety Data Sheet

Name: NFD Hybrid Flooring (SPC)

Product Layer	Name	CAS#	Substance Role
UV Coating	Acematt	7631-86-9	Control the gloss
	Monomer	868-77-9	Synthetic polymer materials, thermosetting coatings and adhesives
	Resin	25068-38-6	Bisphenol a epoxy resin anticorrosion
	Monomer	13048-33-4	Low viscosity, fast solidifying, dilution ability, strengthen the adhesion
	Monomer	15625-89-5	Ultraviolet cure
	Photoinitiator	947-19-3	Hold curing chronic deep curing, yellowing and prolong storage time
Wear Layer	PVC resin	9002-86-2	Wear resistance and prevent slippery
	DOTP	6422-86-2	Increase plastic softness
	Soybean oil	8013-7-8	Increasing the effect of the stabilizer
PVC Film	PVC resin	9002-86-2	Filling material
	titanium oxide	13463-67-7	Enhance product And Ink performance and stability
	printing ink	201058-08-4	Colour film
	Barium sulfate	7727-43-7	
	Calcium Carbonate	471-34-1	
	Aluminium Hydroxide	21645-51-2	
Base Materials	PVC Powder	9002-86-2	Bonding
	Caco3	471-34-1	Filling material, enhance product hardness performance and stability
	calcium-zinc stabilizer	1592-23-0	
	CPE	63231-66-3	Reinforcement
	ACR	9003-01-4	Lubricant, PVC Processing Aid
	G60	9005-08-7	Lubricant
	PE	9002-88-4	Lubricant
	3316A	9002-88-4	Lubricant